



Molded Plastic Manometers Stationary
3% Accuracy for Stationary and Portable Applications

Models Select Chart

Model	Description
MARK II 25	Molded plastic manometer, range 0-3" w.c., red oil, .826 sp. gr.
MARK II 26	Molded plastic manometer, range 0-7" w.c., blue oil, 1.91 sp. gr.
MARK II 27	Molded plastic manometer, range 0-7000 fpm, red oil, .826 sp. gr., requires Pitot tube *sold separately.
MARK II 28	Molded plastic manometer, range 0-10,500 fpm, blue oil, 1.91 sp. gr., requires Pitot tube *sold separately.
MARK II 40-1	Molded plastic manometer, range .1-0-1.0" w.c., red oil, .826 sp. gr.
MARK II 40-1-AV	Molded plastic manometer, range 0-1.1" w.c. & 0-4200 fpm, red oil, .826 sp. gr., requires Pitot tube sold separately.
MARK II 40-250PA	Molded plastic manometer, range 10-0-250 Pa, red oil, .826 sp. gr.
MARK II 40-250PA-AV	Molded plastic manometer, range 0-260 Pa & 0-21 mps, red oil, .826 sp. gr., requires Pitot tube sold separately.
MARK II 40-25MM	Molded plastic manometer, range 0-26 mm w.c., red oil, .826 sp. gr.
MARK II 41-2	Molded plastic manometer, range .2-0-2.4" w.c., blue oil, 1.91 sp. gr.
MARK II 41-2-AV	Molded plastic manometer, range 0-2.5" w.c. & 0-6300 fpm, blue oil, 1.91 sp. gr., requires Pitot tube sold separately.
MARK II 41-600PA	Molded plastic manometer, range 20-0-600 Pa, blue oil, 1.91 sp. gr.
MARK II 41-60MM	Molded plastic manometer, range 0-60 mm w.c., blue oil, 1.91 sp. gr.
MARK II M-700PA	Molded plastic manometer, range 10-0-700 Pa, red oil, .826 sp. gr.
MARK II MM-180	Molded plastic manometer, range 0-180 mm w.c., blue oil, 1.91 sp. gr.
MARK II MM-80	Molded plastic manometer, range 0-80 mm w.c., red oil, .826 sp. gr.

Accessories

Model	Description
A-612	Portable stand.
A-606	Air filter kit for Series Mark II.
A-101	1 oz dispenser bottle of red gage fluid, .826 sp. gr.
A-102	4 oz bottle of red gage fluid, .826 sp. gr.
A-103	1 pt bottle of red gage fluid, .826 sp. gr.
A-104	1 qt bottle of red gage fluid, .826 sp. gr.
A-110	1 oz dispenser bottle of blue gage fluid, 1.910 sp. gr.
A-111	1 pt bottle of blue gage fluid, 1.910 sp. gr.
A-489	4" 303 SS straight static pressure tip with flange.
A-225	Flexible double column plastic tubing, lt. grey, with red color code stripe, 1/8" ID, lengths to 750 ft, per ft.
A-315	Gage connector, shutoff type, for 3/16" rubber tubing.
420706-00	Red pointer indicator.
420706-01	Green pointer indicator.
A-220	Clear flexible vinyl tubing is easily inspected, and is therefore best for test applications where a possibility of fluid entering the tubing exists. 3/16" ID x 5/16" OD, lengths to 500'; 45 psi maximum pressure @ 73°F.
A-480	Plastic static pressure tip.

Specifications:-

INCLINED/VERTICAL

Accuracy	:	±3% FS.
Temperature Limits	:	140°F (60°C).
Pressure Limits	:	10 psi (70 kPa)
Weight	:	1.04 lb (472 g).
Agency Approvals	:	Meets the technical requirements of EU Directive 2011/65/EU (RoHS II).

INCLINED

Accuracy	:	±3% FS
Temperature Limits	:	150°F (65°C)
Pressure Limits	:	15 psi (100 kPa)
Scale Length	:	Approx. 8-1/4" (21 cm)
Weight	:	1.23 lb (558 g)
Agency Approvals	:	Meets the technical requirements of EU Directive 2011/65/EU (RoHS II).